

Ardrox[®] 6076

Natural Citrus Cleaner

PRIMARY APPLICATION

Ardrox[®] 6076 is a 100% organic, biodegradable liquid cleaner. A blend of natural citrus solvents, emulsifiers, and surfactants, it does not contain petroleum-based solvents and removes a wide range of soils, including: oils, grease, chewing gum, tar, inks, adhesives, decals, tire marks, and soap scum. **Ardrox[®] 6076** can be used as a general maintenance cleaner, an immersion cleaner for metal parts, and even a drain cleaner. **Ardrox[®] 6076** is safer to use and easier to dispose of than most petroleum-based or highly alkaline cleaning compounds and has a pleasant citrus odor.

CHEMICAL CHARACTERISTICS

composition.....terpene hydrocarbons and surfactants
 appearance.....clear, orange liquid
 odor.....citrus
 bulk density.....7.0 lbs/gal
 flash point.....120°F T.C.C.

APPLICATION PROCEDURE

Step 1: Clean with **Ardrox[®] 6076**.

Step 2: Rinse with water.

Ardrox[®] 6076 is used either full strength or diluted with water in varying proportions depending upon the surface being cleaned and the soil being removed. The following can be used as a guideline:

Gum:

To remove gum from carpets and other surfaces, first apply **Ardrox[®] 6076**, full strength, on the gum and allow it to penetrate it for 15 to 20 seconds. Then using a clean towel saturated with **Ardrox[®] 6076**, rub briskly. With a clean wet towel, remove as much **Ardrox[®] 6076** as possible. Wipe dry.

Adhesives:

To remove adhesives from aircraft and other surfaces, spray or wipe on **Ardrox[®] 6076** full strength. Wipe off. (Note: Works best on solvent based adhesives.)

General Cleaning:

Ardrox[®] 6076 can be used to clean walls, floors, and other surfaces. Mix 4 to 6 fluid ounces of **Ardrox[®] 6076** per gallon of water. Spray, mop or wipe on the surface. Allow it to penetrate the soil for approximately 5 minutes. Rinse with water.

Immersion:

To clean greasy, oily metal parts, mix 6 to 12 fluid ounces of **Ardrox[®] 6076** per gallon of water. Immerse the parts for as long as necessary (usually 5 to 10 minutes). Drain, rinse, and dry the parts.

Drain Cleaning:

Pour 8 fluid ounces of **Ardrox® 6076** into the drain. Allow it to penetrate the soil for approximately 1 hour. Flush with water. (Note: Do not stand directly over the drain when adding **Ardrox® 6076**.)

NOTE: The above is based upon standard industrial use. Some production operations may require other operating instructions. The Chemetall Oakite Representative will recommend the best way to use this product based upon production requirements.

EFFECTS ON MATERIALS

Ardrox® 6076 may harm some plastics or painted surfaces. Always pretest **Ardrox® 6076** on an inconspicuous area before using on these surfaces.

NOTES ON USE

Do not use around heat, sparks or gas flames.

SAFETY AND HANDLING

Prior to handling and use of any of the materials referenced in this document, the Material Safety Data Sheets should be read and understood by all personnel in contact with these materials.

KEEP OUT OF REACH OF CHILDREN

STORAGE

Dry, indoor storage at temperatures between 40°F and 100°F is recommended, away from any incompatible materials referenced in Material Safety Data Sheets. All containers should be kept tightly closed when not in use.

SHELF LIFE

The shelf life of **Ardrox® 6076** is 3 years.

DISPOSAL

Any disposal of the materials referenced in this document should be in accordance with all applicable federal, state, and local regulations.

Process solutions can contain components other than those present in the materials, as supplied.

Analysis of process solutions may be required prior to disposal.

Oakite Products, Inc. warrants that the product or products described herein will conform with its published specifications. The products supplied by Oakite and information related to them are intended for use by buyers having necessary industrial skill and knowledge. Buyers should undertake sufficient verification and testing to determine the suitability of the Oakite materials for their own particular purpose. Since buyer's conditions of use of products are beyond Oakite's control, Oakite does not warrant any recommendations and information for the use of such products. OAKITE DISCLAIMS ALL OTHER WARRANTIES INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH THE USE OF ITS PRODUCTS.

Chemetall
Oakite



QS-9000 / ISO 9001

Corporate Headquarters and Eastern Branch (800) 526-4473 • Central Branch (Midwest) (877) 941-3800
Western Branch (800) 331-1197 • Oakite Canada Limited (800) 668-4318 • Chemetall Mexicana 011 52 55 5656 1490
Website: www.oakite.com • E-mail: oakite.products@chemetall.com • Shop online at www.oakitestore.com